



ATS-20T

Order No.: 0255650

PRODUCTINFOS

16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- High operating range
- Frequency range perfectly adapted to voice transmissions
- Parallel operation of up to 4 different channels possible without any interference
- Extra small and lightweight transmitters and receivers
- Licence-free in the EU

16-channel miniature transmitter,

for microphone operation and audio line signals.

- Supplied with electret tie clip microphone
- Microphone input/audio line input via 3.5 mm jack with automatic detection, depending on the configuration (mono/stereo)
- LCD for indicating channel and battery status

- Mute button
- Lanyard
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 100 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

ATS-20T

General information

Description	16-channel digital miniature transmitter
Carrier frequency range	863-865 MHz
Channels	1
Operating time	> 15 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	≤ 10 mW
--------------------	--------------

ATS-20T

Operating range	100 m
Power supply transmitter	integrated rech. lithium batt. (3.7 V/600 mAh)
Width transmitter	40 mm
Height transmitter	80 mm
Depth transmitter	12 mm
Weight transmitter	37 g
Connections transmitter	3.5 mm jack (microphone/line in), micro USB charging port

ATS-20T

EAN code	4007754239676
Net weight	0.054 kg