



## VS-211H2

2x1 4K HDR HDCP 2.2 HDMI Auto Switcher

| HDMI | HDCP Compliant | 4K/60 UHD (4:2:0)  
| 4K/60 UHD (4:4:4) | HDCP 2.2 Compatible



VS-211H2 is a high-performance auto switcher for 4K@60Hz (4:4:4) HDMI video signals. Offering priority and last-connected auto switching scheme options, it automatically switches input signals to output connection, according to the selected switching scheme, and based on active video signals detection

### FEATURES

**HDMI Signal Switching** - HDR and HDCP 2.2 compliant, it supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0

**Multi-channel Audio Switching** - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

**I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling, processing, locking and pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

**Cost-Effective Maintenance** - Status LED indicators for HDMI ports facilitate easy local troubleshooting

**Easy Installation** - Compact DigiTOOLS® fan-less enclosure fits for convenient under tables or dropped-ceiling mounting, or side-by-side mounting of 3 units in a 1U rack space with the recommended rack adapter



## TECHNICAL SPECIFICATIONS

---

|                          |                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inputs                   | 2 HDMI On female HDMI connectors                                                                                                                                                                                                                                                                                                           |
| Outputs                  | 1 HDMI On a female HDMI connector                                                                                                                                                                                                                                                                                                          |
| Ports                    | 2 Contact-Closure Switches On a 3-pin terminal block connector for remote device operation                                                                                                                                                                                                                                                 |
| Video                    | Max. Data Rate 17.82GBPS (5.94Gbps per graphic channel)<br><br>Max. Resolution 4K@60Hz (4:4:4)<br><br>HDMI Support Deep Color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0<br><br>Standards Compliance HDR10, HDCP 2.2 (does not support conversion to HDCP 1.4) |
| User Interface           | Controls: Status/priority DIP-switches, contact closure remote control                                                                                                                                                                                                                                                                     |
| REGULATORY               | Certification EMC EN 55032, IEC 60950-1(ed.2), IEC 60950-1(ed.2)am1, IEC 60950-1(ed.2)am2                                                                                                                                                                                                                                                  |
| Environmental Conditions | Operating Temperature 0° to +40°C (32° to 104°F)<br><br>Storage Temperature -40° to +70°C (-40° to 158°F)<br><br>Humidity 10% to 90%, RHL non-condensing                                                                                                                                                                                   |
| Power                    | Consumption 5V DC, 560mA                                                                                                                                                                                                                                                                                                                   |
| Accessories              | Included Power adapter                                                                                                                                                                                                                                                                                                                     |
| Product Dimensions       | 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H                                                                                                                                                                                                                                                                                 |
| Product Weight           | 0.2kg (0.4lbs) approx                                                                                                                                                                                                                                                                                                                      |
| Shipping Dimensions      | 49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15" ) W, D, H                                                                                                                                                                                                                                                                             |
| Shipping Weight          | 0.6kg (1.4lbs) approx                                                                                                                                                                                                                                                                                                                      |



