



ATT100

Order No.: 0259864

PRODUCTINFOS

Tour guide transmitter

- 10+10 pre-programmed channels, channels 1-10 are transmitting with low power (operating range: approx. 200 m), channels 11-20 are transmitting with increased power (PMR446 standard: high operating range of up to 2 km)
- High battery capacity for continuous announcements of up to 6 hours
- Fully programmable (depending on the application)
- 3 different operating modes can be selected:
 - Continuous transmission
 - Voice control
 - Control via push-to-talk buttons (PTT)
- Matching the tour guide receiver ATR200
- Supplied with belt clip, lanyard

Licence-free, please refer to instruction manual on MONACOR's website.

Manufacturer information:

Alan Electronics GmbH
Daimlerstrasse 1 g
63303 Dreieich
Germany
info@albrecht-midland.de

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

ATT100

General information

Description	20-channel tour guide transmitter
Carrier frequency range	446.00625-446.1 MHz
Channels	1
Admiss. ambient temp.	-10 °C to +40 °C

Specifications transmitter

Transmitting power	10 mW/100 mW
Operating range	200 m/2 km
Power supply transmitter	1,200 mAh rech. lithium-ion batt.

ATT100

Width transmitter	83 mm
Height transmitter	52 mm
Depth transmitter	27 mm
Weight transmitter	150 g
Connections transmitter	4-pole headset jack, DC charging socket

ATT100

EAN code	4032661299024
Net weight	0.179 kg