



# kramer

## PT-102SN

1:2 s-Video Distribution Amplifier

---



The PT-102SN is a high-performance video distribution amplifier for s-Video (Y/C) video signals. The unit takes one input, provides correct buffering and isolation, and distributes the signal to two identical outputs

## FEATURES

---

Bandwidth (Y) - 150MHz (-3dB)

Y & C Level (Gain) Controls

Ultra Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter



# kramer

## TECHNICAL SPECIFICATIONS

---

|                       |  |
|-----------------------|--|
| INPUT:                | 1 s-Video on a 4-pin connector                                   |
| OUTPUTS:              | 2 s-Video on 4-pin connectors                                    |
| MAX. OUTPUT LEVEL:    | 1.3Vpp   |
| BANDWIDTH (-3dB):     | 150MHz   |
| DIFF. GAIN:           | 0.05%  |
| DIFF. PHASE:          | 0.05Deg  |
| K-FACTOR:             | <0.05%   |
| S/N RATIO:            | 76dB @5MHz   |
| CONTROLS:             | Gain: luma (Y) -1.9dB to +5.1dB; chroma (C) 0dB to +6.8dB, @5MHz |
| COUPLING:             | AC   |
| POWER CONSUMPTION:    | 12V DC, 25mA   |
| INCLUDED ACCESSORIES: | Power supply, mounting bracket                                   |
| OPTIONS:              | RK-4PT 19" rack adapter  |
| Product Dimensions    | 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H        |
| Product Weight        | 0.1kg (0.3lbs) approx  |
| Shipping Dimensions   | 17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39" ) W, D, H      |
| Shipping Weight       | 0.4kg (0.8lbs) approx  |

