DATA SHEET

PanaCast® 2 Camera





180° Panoramic Field of View

The PanaCast® 2 camera is a Plug-and-Play USB device that connects directly to your PC or Mac. It delivers a Panoramic-4k quality video stream along with high fidelity stereo audio.

PanaCast 2 transforms how we see and connect electronically. It lets you add the natural human field of view to your meetings and gatherings with a simple Plug-and-Play device.

Use it to improve your video collaboration experience with popular apps and services such as Skype® for Business, Skype®, Cisco WebEx®, Citrix® GoToMeeting®, Google® Hangouts™, Facebook®, and more. Simply plug in and go, without the need to download or install any drivers or software to get started.

Conventional cameras typically deliver a narrow field of view. PanaCast 2 gives you an ultra-wide field of view so you can see more of what you need to see.

Benefits

- Immersive 180° x 54° view
- Plug-and-Play
- USB 3.0 and USB 2.0
- Up to 4.15 MP video
- Better video at all resolutions
- HD quality stereo audio built-in
- Works with Microsoft® Lync®, Skype®, Cisco WebEx®, Citrix® GoToMeeting®, Google® Hangouts™, Facebook®,...







Narrow Field of View - Video from three conventional cameras



The PanaCast 2 panoramic experience

The PanaCast 2 camera produces panoramic video by combining video streams from three imagers simultaneously and processing these in the PanaCast video processor on-board to dynamically stitch, optimize and render the video to a mathematically-correct cylindrical projection with ultra-low latency of <~5ms from photons to USB data.

Camera Specifications

Tech Specifications

- Panoramic-4k: 3840 x 1088; 4.15 MP YUV 4:2:2, MIPEG
- HD: 1920 x 1088; 2.1 MP YUV 4:2:2, MJPEG
- ~180° (H) x 54° (V)
- 188° DFOV
- Adjustable FOV through UVC PTZ command set
- Frame rate up to 30fps
- Latency: <= 5ms
- 5V Power Jack
- 0.3m to Infinity Fixed Focus (each imager)
- 10 Lux
- Motion JPEG Built-in
- Auto 50/60 Hz Detect Built-In
- Color Controls
 - Sharpness
 - Brightness
 - Gamma
 - Saturation Control
 - White Balance (Man.)
- Status Indicator
 - LEDs Built-in
 - Lightweight ePTZ App (optional)
- Product Certifications
 - FCC Part 15 Class A (for commercial use only)
 - ROHS, REACH Compliant

System Requirements

- Plug-and-Play for Windows and Mac applications
- Supports USB Video Class (UVC) Driver
- USB 2.0/3.0
- Windows 7,8,8.1 or later
- Mac OS X 10.9 or later

Product Information

Weight: 125gWidth: 60 mm

Height: 25 mm

Length: 74 mm

Operating Temperature: 0° C - 40° C

Operating Humidity: 15%-85% (Non-Condensing)

What's In The Box?

- PanaCast[®] 2 Camera
- Table Stand/Wall Mount
- Quick Reference Guide
- USB 3.0 cable
- Power Adapter

Warranty

• You can find a detailed description of our Warranty.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation



About Altia Systems



Altia Systems, Inc. 10020 N. De Anza Blvd, Suite 200 Cupertino, CA 95015 1-408-996-9710 www.getpanacast.com



Altia Systems® (getpanacast.com) is a venture-backed company based in Cupertino, CA, and is the creator of the PanaCast® Experience solution. The award-winning PanaCast® offers a unique experience that enables anyone on desktop or mobile to communicate in interactive, real-time Panoramic-HD 200° field-of-view video that replicates the human panoramic perspective.