



ATS-80R

Order No.: 0250001

PRODUCTINFOS

42-channel digital PLL voice transmission system, 823-832 MHz and 863-865 MHz

- As a tour guide system also suitable for any other application in which a two-way communication is required, e.g. training sessions, lectures with questions and answers and group tours or factory tours
- High resistance to interference due to digital transmission
- High operating range
- Frequency range optimised for voice transmissions
- Interference-free parallel operation of up to 42 different channels possible

42-channel PLL receiver

- Supplied with matching earphone
- Adjustable headphone output
- Automatic switch-off (power-saving function)
- High-contrast OLED display
- Battery status indication
- Push-to-talk button with 3 operating modes (PTT, PTB, PTM)
- Alarm-off button
- Operating range alert

ATS-80R

Carrier frequency range	823-832 MHz, 863-865 MHz
Audio frequency range	300-4,500 Hz
Channels	1
Operating time	> 30 h
Admiss. ambient temp.	0-40 °C

Specifications receiver

Power supply receiver	2 x 1.2 V NiMH rech. batt. AA size
Width receiver	47 mm
Height receiver	109 mm
Depth receiver	35 mm
Weight receiver	53 g
Connections receiver	3.5 mm jack (earphones)

ATS-80R

EAN code	4007754273809
Net weight	0.079 kg