



## RU-850LTH/5

Order No.: 0259560

### PRODUCTINFOS

#### **Dynamic hand-held UHF PLL microphone transmitter**

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Lock function/mute function
- Special design to reduce handling noise, structure-borne noise and acoustic feedback
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

#### **Manufacturer information:**

JTS PROFESSIONAL CO., LTD.  
No. 148, Gongye 9th Rd., Dali Dist.

41280 Taichung City  
Taiwan  
jts@jts.com.tw

**EU-Representative:**

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Germany  
info@monacor.com

**Safety Notes and Warning Messages**

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

**TECHNICAL SPECIFICATIONS****RU-850LTH/5**

Description	hand-held microphone
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	30 h
Audio frequency range	50-16,000 Hz
Max. sound pressure	148 dB
Housing material	plastic
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 51 mm x 269 mm
Weight	242 g

**RU-850LTH/5**

Packaging dimensions (W x H x L) 0.1 x 0.075 x 0.3 m

Gross weight 0.54 kg

Net weight 0.285 kg

**RU-850LTH/5**

EAN code 4007754263107

Net weight 0.285 kg