



## ATS-22R

Order No.: 0257110

### PRODUCTINFOS

#### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

#### 16-channel miniature receiver,

with intercom function.

- Intercom function with transmitter ATS-22T via push-button
- Built-in microphone
- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option

- Dimensions: 40 x 87 x 12 mm

### Licence-free in the EU.

### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Germany  
info@monacor.com

### Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

## TECHNICAL SPECIFICATIONS

### ATS-22R

#### General information

Description	16-channel digital miniature receiver
Carrier frequency range	863-865 MHz
Channels	1
Operating time	> 15 h
Admiss. ambient temp.	0-40 °C

#### Specifications receiver

Power supply receiver	integrated rech. lithium batt. (3.7 V/600 mAh)
Width receiver	40 mm
Height receiver	87 mm
Depth receiver	12 mm
Weight receiver	37 g
Connections receiver	3.5 mm jack (earphone), micro USB charging port

**ATS-22R**

EAN code

4007754246230

Net weight

0.052 kg