



kramer

VM-24HC

2x1:4 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM-24HC is a high-performance switcher and distribution amplifier for HDMI signals. The unit accepts one of two HDMI inputs and distributes the selected signal to four HDMI outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphics channel)

HDTV Compatible

HDCP Compliant

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

EDID Handling - Acquires the EDID from one output, from all connected outputs (auto-mix) or uses a default EDID

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

HDMI Support - With Deep Color, x.v.Color™, up to 7.1 Uncompressed Audio Channels

3D Pass-Through

Flexible Control Options - Front panel, IR remote & RS-232

Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



kramer

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|--|
| INPUTS: | 2 HDMI connectors |
| OUTPUTS: | 4 HDMI connectors |
| MAX. DATA RATE: | 6.75Gbps (2.25Gbps per graphic channel) |
| COMPLIANCE WITH HDMI STANDARD: | Supports HDMI and HDCP |
| CONTROLS: | EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR |
| INDICATORS: | POWER, IR, OUTPUT LEDs |
| POWER CONSUMPTION: | 5V DC, 1.1A |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| Accessories | Included Power supply |
| Product Dimensions | 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H |
| Product Weight | 0.9kg (1.9lbs) approx |
| Shipping Dimensions | 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H |
| Shipping Weight | 1.4kg (3.0lbs) approx |



