



## TG-10STX/1

Order No.: 0173730

### PRODUCTINFOS

#### 16-channel PLL Tour Guide System, 863-865 MHz

- With extensive accessories
- Operating range: up to 60 m
- Parallel operation of up to three wireless transmitters
- Licence-free in the EU

#### 16-channel PLL wireless transmitter

- 2 inputs (CH1/CH2) via rear comb. jacks, with level controls
- 1 input (CH3) via 6.3 mm mono jack
- Continuously adjustable headphone output
- 2 loop outputs
- Phantom power can be activated as required

**Licence-free in the EU.**

**Manufacturer information:**

JTS PROFESSIONAL CO., LTD.  
No. 148, Gongye 9th Rd., Dali Dist.  
41280 Taichung City  
Taiwan  
jts@jts.com.tw

**EU-Representative:**

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Germany  
info@monacor.com

**Safety Notes and Warning Messages**

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

**TECHNICAL SPECIFICATIONS****TG-10STX/1**

## General information

Description tour guide system wireless transmitter

Carrier frequency range 863-865 MHz

Audio frequency range 40-15,000 Hz

Channels 2

Admiss. ambient temp. 0-40 °C

## Specifications transmitter

Operating range 60 m

Power supply transmitter via encl. power supply

Width transmitter 214 mm

**TG-10STX/1**

Height transmitter	45 mm
Depth transmitter	240 mm
Weight transmitter	1.3 kg
Connections transmitter	2 x comb. jack (input CH1/CH2), 1 x 6.3 mm mono jack (input CH3), 1 x 3.5 mm stereo jack (headphones), 2 x 6.3 mm mono jack (loop outputs)

**TG-10STX/1**

EAN code	4007754229424
Net weight	1.415 kg